



OA 7745 Permaflat Matt Enamel

Product Data

Description

This is a high quality alkyd enamel paint which will provide a hard wearing, fully washable and attractive finish. It can be safely used in aggressive interior and exterior environments. Permaflat is a truly versatile top coat.

Recommended uses

Permaflat can be applied on all suitably prepared and primed surfaces. Timber, metal, plaster and cementitious substrates. It can be used in aggressive areas such as kitchens, bathrooms, laundries as well as sensitive areas like nurseries & bedrooms.

Principal Properties :

1. Good covering power
2. Attractive finish
3. Complete washability
4. Excellent durability
5. Easy to apply
6. Good levelling and drying properties.
7. Provides long term protection in aggressive environments.
8. Resists steam and condensation.
9. Lead free

Application methods : Brush ,Roller & Spray

Dilute with AM 15 (or similar) only as required to achieve good workability or an even spray pattern.

Surface Preparation :

Substrates to be properly primed and prepared. Existing paints to be sound. Clean and degrease surfaces to remove all types of contamination. De-dust after smoothing or sand papering.

Physical Data

Volume Solids 45.44% (ASTM D 2697)*

Finish Flat

Colour As per colour card

Spreading rate
@ 25 microns DFT..... 18.17 m² /Lt

Drying time.....
To Touch..... 2 hours
To re-coat..... 12 hours

- Depending on ambient temperature & surface conditions

Thinners AM 15, White Spirit or similar

Flash Point..... 38°C

Application method Brush, Spray/Roller

Packing size..... 18 Ltr/ US Gallon

Shelf life 12 months

Storage Out of sun light

Storage Temp 5°C upto 40°C

Note : Allow for application losses. ie. conditions, surface irregularity, surface porosity and application method.

- * Volume solids is measured in accordance with ASTM-D-2697. Slight variations may occur due to colour and testing variances.