



# Amertex 2269 Textured Finish Medium (Exterior/Interior)

## Product Data

### Description

This durable and attractive finish is based on a Vinyl Versatate Acrylic Copolymer resin. The material is hard wearing, washable and fully resistant to aggressive exterior environments. This product is filled with graded natural stone. It is developed to give various textured finishes. Excellent colour retention makes Amertex 2269 a self finishing system.

### Recommended uses

Can be used on Plaster, cementitious substrates, masonry, Primed wood or steel etc. Good for outside walls, boundary walls or for inside use such as ceilings or features.

### Principal Properties :

1. Durable & weather resistant
2. Almost odourless
3. Excellent colour retention
4. Ease of application
5. Can be used inside and outside
6. Economical & inexpensive to apply
7. Good adhesion properties
8. Water vapour permeable
9. Washable

### Application methods :

Roller or Air mix spray ( Hopper or Pressure System).  
Texture can be varied by depth and application technique.  
Dilution with sweet water to be limited to the need to achieve workability or texture adjustment.

### Surface Preparation :

- a. **Concrete, Plaster etc** : Neutralize as required. Fill and smooth. Prime to suit interior or exterior surfaces. Clean off all contamination, de dust.

Recommended Primers : OA 3587 Latex Primer Sealer or  
OA 3566 Acrylic Primer Undercoat.

- b. **Steel** : Prepare and Prime in accordance with primer data sheet. ie. OA 3957. Red Oxide.

### Physical Data

Solid Content ..... Appro.78.62% (by weight)  
(Varies slightly according to colour)

Finish ..... Texture Medium

Colours..... See Color Card

Spreading rate ..... 1.0 - 1.8 m<sup>2</sup> /Kg

- Depending on colour, application method, surface condition & required texture.

#### Drying time :

To Touch..... 2 hours  
To re-coat..... 24 hours

- Depending on thickness and ambient conditions.

Thinners ..... Sweet Water

Flash Point..... Non Flammable

Application method ..... Roller or  
Spray

Packing size..... 25 Kg

Shelf life ..... 12 months

Storage ..... Out of sun light

Storage Temp ..... 5°C upto 40°C