



Amertex 2269 MP Texture

(Exterior/Interior)

Product Data

Description

This durable and attractive finish is based on a Vinyl Versatate Acrylic Copolymer resin. The material is hard wearing, washable and fully resistant to aggressive exterior environments. This product does not contain sand or coarse particles. The coating is formulated to spray to an attractive rounded finish and is capable of being flattened off to provide a pressed texture finish. With a topcoat it can be given an attractive gloss appearance.

Recommended uses

Can be used on Plaster, cementitious substrates, masonry, primed wood or steel etc. Good for outside walls, boundary walls or for inside use such as ceilings or features.

Principal Properties :

1. Durable & weather resistant
2. Almost odourless
3. Excellent colour retention
4. Ease of application
5. Can be used inside and outside
6. Economical & inexpensive to apply
7. Good adhesion properties
8. Water vapour permeable
9. Washable.
10. Can be supplied in flat or (when top coated) in gloss.

Application methods :

Roller or Air mix spray (Hopper or Pressure System).
Texture can be varied by depth and application technique. Pressed finish can be achieved by flattening by roller(solid) or by float. Dilution with sweet water to be limited to the need to achieve workability or texture adjustment.

Surface Preparation :

- a. **Concrete, Plaster etc** : Neutralize as required. Fill and smooth. Prime to suit interior or exterior surfaces. Clean off all contamination, de dust.

Recommended Primers : OA 3587 Latex Primer Sealer or
OA 3566 Acrylic Primer Undercoat.

- b. **Steel** : Prepare and Prime in accordance with primer data sheet. ie. OA 3957. Red Oxide.

Top coats:

When a gloss finish is required apply OA 7390 Supermastic Gloss Acrylic Emulsion. If any extra gloss or additional protection is required apply AM 450X Aliphatic polyurethane instead. In order to achieve a closed film matt finish apply OA 6542 Permastic Vinyl Acrylic Emulsion or OA 6425 Supermastic Vinyl Acrylic Emulsion.

mp2269.DOC - PD 1/97

Physical Data

Solid Content Appro.75.62% (by weight)
(Varies slightly according to colour)

Finish Rounded or flattened texture
Flat or Gloss if topcoated.

Colours..... See Color Card

Spreading rate 1.0 - 1.5 m² /Kg

- Depending on colour, application method, surface condition & required texture.

Drying time :
To Touch..... 2 hours
To re-coat..... 24 hours

- Depending on thickness and ambient conditions.

Thinners Sweet Water

Flash Point..... Non Flammable

Application method Spray

Packing size..... 25 Kg

Shelf life 12 months

Storage Out of sun light

Storage Temp 5°C upto 40°C